



# XP7000 Series

Intel Atom

## INDUSTRIAL PANEL PC

17.0" XGA LCD Display (LED)  
5 Wire Resistive Touch Screen

Intel Atom N270 1.6GhzCPU

Fan-less Design

IP65 Powder Coated  
Aluminium or Optional  
Stainless Steel Front Panel

One Gigabit Ethernet Port  
Four Communication Ports  
4 x USB, 1 x VGA, Audio I/O

1 x PCI Expansion Slot

Stainless Steel Chassis with  
85mm depth



RS232/422/485



**IP65**



The XP7000 Series Fan-less Industrial Workstations incorporating 17.0" LED illuminated displays and the Intel Atom N270 processor are ideal for HMI applications.



Available with IP65 cast aluminium or stainless steel front panels and complimented with an all stainless steel chassis the Fan-less XP7000 delivers an extensive feature set to meet the most demanding of applications. Equipped with a 320GB 2.5" SATA Hard Disk Drive as standard and options for a Slim-line Optical Drive, DVD-ROM and Compact Flash the system offers exceptional storage capacity; up to 2GB of system memory also ensures agile processing performance. Extensive I/O support for Multiple Serial, USB 2.0, Ethernet, HDMI, Audio Interface, External Monitor and PCI Slot expansion further enhance flexibility.

The logical design ensures easy maintenance and includes an easy to change dust filter mechanism without the need to open the chassis. With all models meeting high shock and vibration specifications the XP7000 is ideal for a range of industrial and heavy duty commercial applications.

MODEL	XP7102NF
<b>CPU</b>	Intel® Atom N270 1.6GHz
<b>Chipset</b>	Intel® 945GSE + ICH7M
<b>Memory (standard)</b>	1G DDR2 SODIMM, Up to 2GB
<b>Storage</b>	320 GB 2.5" SATA HDD (standard) / DVD-ROM optional
<b>Expansion Slot</b>	1 x PCI
<b>Housing</b>	Aluminium front panel & stainless steel chassis
<b>Cooling</b>	Fan-less thermal conduction
<b>I/O Port</b>	1 x Ethernet 10/100/1000M (RJ45) 4 x USB 2.0, VGA (DB15) with Dual View support, PS2 K&M 1 x RS232/422/485, 3 x RS232 Audio In/Out
<b>Power input</b>	100-240VAC / 24VDC optional
<b>Installation Type</b>	Rack Mount / VESA
DISPLAY	
<b>Display type</b>	17.0" XGA TFT LED illuminated LCD
<b>Resolution</b>	1280 x 1024
<b>Brightness</b>	250cd/m <sup>2</sup>
<b>Touch Screen</b>	5-Wire, Resistive
SIZE AND WEIGHT	
<b>Dimension (WxHxD)</b>	442mm x 354mm x 85mm
<b>Cut-out Size (WxH)</b>	410mm x 311mm
<b>Weight</b>	8.9kg
ENVIRONMENT	
<b>Operating Temperature</b>	0-50°C
<b>Storage Temperature</b>	0-70°C
<b>Humidity</b>	10-85% (Non-condensing)
<b>Front Panel Protection</b>	IP65
<b>Certification</b>	FCC, CE

## NemaVision-iPC

27 Hercules Way  
Aeropark  
Farnborough GU14 6UU  
United Kingdom

**T:** +44 (0)1252 370030

**F:** +44 (0)1252 373767



DST-XP7102-Rev. A : NemaVision-iPC is a trading name of Nematron Europe Ltd.