


cMT-iV5

Cloud Human Machine Interface

Breakthrough the traditional architecture of one machine terminal with one touch panel

The connection between cMT-SVR and cMT-iV5 via 1G Ethernet constructs a powerful multi-processing architecture of HMI. The cMT-SVR can flexibly combine with cMT-iV5 and iPad to enhance its operational efficiency.



■ The monitoring center of HMIs

Integrated with all cMT-SVRs based on the distributed architecture, the cMT-iV5 can monitor all the operational status of machines at the same time.

■ Unprecedented operating experience

The capacitive touch panel made of tempered glass is very durable. The Multi-Touch panel makes your touch experience extremely smooth and easy like using an iPad.

Integration

Distributed


Flexible combination

■ Perfect integration of hardware and software brings the ultra-high performance of cMT-iV5


Equipped with the powerful Cortex A9 1GHz Dual-Core processor and high resolution 1024x768 display, the cMT-iV5 not only perfectly monitors the machine's operation, but also you can easily design an ideal project with WEINTEK configuration software : EasyBuilder Pro.




Dimensions




Front View



Rear View



Bottom View



Cutout Dimensions

Specification

Display	Display	9.7" TFT
	Resolution	1024 x 768
	Brightness (cd/m ²)	350
	Contrast Ratio	500:1
	Backlight Type	LED
	Backlight Life Time	>30,000 hrs.
Touch Panel	Colors	262K
	Type	Tempered Glass, Capacitive Type
Memory	Accuracy	Active Area Length(X)±2%, Width(Y)±2%
	Storage (MB)	512 MB
Processor	RAM (GB)	1 GB
		32 bits RISC Cortex A9 1GHz
I/O Port	SD Card Slot	N/A
	USB Host	N/A
	USB Client	N/A
	Ethernet	10/100/1000M
	COM Port	N/A
	Audio Output	Built-in Mono Speaker
RTC	Video Input	N/A
		Built-in
Power	Input Power	24±20%VDC
	Power Isolation	Built-in
	Power Consumption	900mA@24VDC
	Voltage Resistance	500VAC (1 min)
	Isolation Resistance	Exceed 50MΩ at 500VDC
Specification	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
	Enclosure	Plastic
	Dimensions WxHxD	257.2 x 199.7 x 32.7mm
	Panel Cutout (mm)	248.5 x 191mm
Environment	Weight (kg)	Approx. 0.76 kg
	Protection Structure	NEMA4 / IP65
	Storage Temperature	-20° ~ 60°C (-4° ~ 140°F)
	Operating Temperature	0° ~ 50°C (32° ~ 122°F)
Certificate	Relative Humidity	10% ~ 90% @ 40°C (non-condensing)
		CE marked
Language	Display	English, French, Italian, Spanish, Russian, Simplified Chinese, Traditional Chinese, Korean, Deutsch
	Input Methods	English, French, Italian, Spanish, German, Russian, Pinyin, Zhuyin
Ordering Information	cMT-iV5	• 512MB flash memory • 1GB RAM on board • 10/100/1000M Ethernet port x 1
	Cloud Human Machine Interface	
	cMT-SVRiV5	• cMT-SVR x 1 • cMT-iV5 x 1 • Ethernet cable 2m x 1
	cMT-SVR & cMT-iV5 Bundle Package	

* Specifications subject to change without notice.



WEINTEK LABS., INC.

Address: 9F., No.910, Zhongzheng Rd., Zhonghe Dist.,
New Taipei City 23586, Taiwan
www.weintek.com

Tel: +886-2-22286770 Fax: +886-2-22286771
Sales: salesmail@weintek.com
Product Support: servicemail@weintek.com



ISO 9000: 2008

English | Jan 2014