# Order Number Generation

Base unit configuration: ePCx00T-CM440-2GB-40SS-XP, where **x** = 12, 15, 17, or 19 (for display size), includes a touchscreen, Celeron M 440, 2 GB DRAM, 40 GB SATA Solid State Drive, and Windows XP Pro.

*e*PC ___ ___ - ___ ___ ___ ___ ___ ___ ___

Display Size:

1200	12.1" SVGA LCD
1500	15.0" XGA LCD
1700	17.0" SXGA LCD
1900	19.0" SXGA LCD

Input Options:

T	Touchscreen
blank	None

Processor:

CM440	Celeron M 440
T2500	Core Duo T2500

DRAM Options:

-2GB	2 GB DRAM

Hard Drive:

-40SS	40 GB SATA Solid State Drive [1]
-80SS	80 GB SATA Solid State Drive [1]
-160SS	160 GB SATA Solid State Drive [1]
blank	250 GB (minimum) SATA hard drive

Operating System:

-XP	Windows XP Professional
-W7	Windows 7 Professional (32-bit)
-NOS	No OS installed

Power Supply:

blank	120-240 VAC
-DC	24 Volt DC

Front Panel:

blank	Powder Coated Aluminum
-NL	Powder Coated Aluminum w/o Logo
-SS	Machined 304 Stainless Steel
-RM	Rackmount Powder Coated Aluminum (ePC1900 only) [2]

[1] Solid State Drive options carry a 5-year (part only) warranty.
[2] Rackmount front panel is not NEMA 4/4x/12 and the unit is required to be installed on a rack in a Type 1 enclosure.